

Basecoat 456 – Floor Sealer

1. IDENTIFICATION OF THE SUBSTANCE OR PREPARATION AND OF THE COMPANY

Identification of Preparation: Basecoat 456
Date of Safety Data Sheet: December 23, 2024
Use of Preparation: Floor Sealer
Company Identification: Parkside Professional Products Ltd.
4777 Kent Avenue
Niagara Falls, Ontario L2H 1J5
OFFICE: 905-358-8364

Company Emergency Telephone Number Emergency Phone: 905-358-8364

Transportation Emergency Telephone Number CANUTEC 613-996-6666 or * 666 for cell phone

2. HAZARD IDENTIFICATION

Emergency Overview:

OSHA / WHMIS 2015 Hazards

Not hazardous.

Classification of substance or mixture

GHS-US/Canadian classification:

Not hazardous

Label Elements

GHS-US Labeling

Hazard Pictograms (GHS):

None.

Signal Word (GHS):

None

Hazard Statements (GHS):

None

Precautionary Statements (GHS):

P264: Wash thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response (GHS):

P301+P312: IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

P302 + P352: IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention.

P330: Rinse mouth.

P501: Dispose of contents / container in accordance with local regulations.

Basecoat 456 – Floor Sealer

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Description: Chemical Blend

Ingredient	CAS#	% by Wt	Classification
Diethylene Glycol Monoethyl Ether	111-90-0	1-5	Acute Toxicity Category 5 (Oral) - H303 Skin Irritation Category 2 – H315 Eye Irritation Category 2B– H320
Tributoxy Ethyl Phosphate	75-51-3	1-5	Skin Irritation Category 2 – H315 Eye Irritation Category 2A– H319 STOT Single Exposure Category 3 – H335
Trimethyl Pentanyl Disobutyrate	6846-50-0	1-5	Skin Irritation Category 3 – H316 Eye Irritation Category 2B – H320
Acrylic Polymer	None	15-35	Not regulated.

4. FIRST AID MEASURES

Inhalation:	Remove to fresh air. If symptoms persist consult physician.
Eye Contact:	Remove contacts. Flush with water for at least 20 minutes, occasionally lifting the upper and lower eyelids. Repeat if required. If irritation persists get medical attention.
Skin Contact:	Thoroughly wash exposed skin with soap and water. Remove any contaminated clothing and wash before reuse.
Ingestion:	Wash out mouth with water. Drink plenty of water. Do not induce vomiting unless directed by medical personal. Never give anything to an unconscious person. Get medical aid.
Notes to Physician:	Treatment based on judgment of attending physician.

5. FIRE FIGHTING MEASURES

Suitable extinguishing media:	Flood with water for extinguishing agent. CO2, dry chemical, alcohol resistant foam
Unsuitable extinguishing media:	None known.
Special exposure hazards	Thermal decomposition releases irritating gases.
Special safety equipment:	Self-contained positive pressure breathing apparatus and protective clothing.
Fire and explosion	Not flammable. Not an explosive hazard.
Further information	Keep containers and surrounding cool with water spray.

Basecoat 456 – Floor Sealer

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not get in eyes, on skin, or on clothing. Do not breathe vapour or mist.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area.

Environmental Precautions

Prevent entry to sewers and public waters.

Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clear up spills immediately with absorbent and dispose of waste safely.

Reference to Other Sections: See Heading 8. Exposure controls and personal protection.

7. HANDLING AND STORAGE

Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Avoid splashes or spray in enclosed areas.

Information about fire and explosion protection:

Keep respiratory protective device available.

No special measures required.

Conditions for safe storage, including any incompatibilities:

Storage: Acids, Oxidizers, reducing agents.

Requirements to be met by storerooms and receptacles:

Store in a cool location.

Protect from humidity and water.

Unsuitable material for receptacle: steel.

Unsuitable material for receptacle: aluminium.

Avoid storage near extreme heat, ignition sources or open flame.

Information about storage in one common storage facility:

Do not store together with alkaline products or strong acids.

Store away from oxidizing agents.

Store away from foodstuffs.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Store receptacle in a well ventilated area.

Keep container tightly sealed.

Specific end use(s) No further relevant information available.

Basecoat 456 – Floor Sealer

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection:	Use local exhaust or dilution ventilation.
Hand protection:	Chemical resistant gloves.
Eye protection:	Safety goggles or full face shield.
Skin protection:	Use body-covering impervious clothing.
Working hygiene:	Take usual precautions when handling. Workers should wash hands before eating, drinking or smoking.
Exposure Guidelines:	

Diethylene Glycol Monoethyl Ether: ACGIH TLV – STEL: 150 ppm TWA: 100 ppm
 OSHA PELs – TWA: 100 ppm TWA: 600 mg/m³

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical State	Liquid	Odour	Mild Acrylic
Appearance	Milky White	Odour Threshold	No data available.
Colour	Milky White	Remarks/Method	
Property	Values		
pH	8.50-9.00	None known	
Melting/Freezing Point	No data available	None known	
Boiling Point/Range	No data available	None known	
Flash Point	Not applicable.	None known	
Evaporation Rate	Similar	None known	
Flammability (solid, gas)	Flammable	None known	
Flammability Limit in Air:			
Upper Limit	No data available	None known	
Lower Limit	No data available	None known	
Vapour Pressure	No data available	None known	
Vapour density	No data available	None known	
Specific Gravity	0.998-1.04 g/cm ³		
Water Solubility	Soluble in water.	None known	
Solubility Other Solvents	No data available	None known	
Partition Coefficient:			
n-octanol/water	No data available	None known	
Autoignition temperature	No data available	None known	
Decomposition Temperature	No data available	None known	

Basecoat 456 – Floor Sealer

Kinematic Viscosity	No data available	None known
Dynamic Viscosity	No data available	None known
Explosive Properties	No data available	None known
Oxidizing Properties	No data available	None known

Other Properties:

Softening Point	No data available
VOC Content %	No data available
Particle Size	No data available
Particle Size Distribution	No data available

10. STABILITY AND REACTIVITY

Reactivity	The substance decomposes on heating, on contact with acids and under influence of light producing toxic and corrosive gases including. The substance is a strong oxidant and reacts with combustible and reducing materials.
Chemical stability	Stable under recommended handling and storage conditions (see section 7).
Thermal decomposition/conditions to avoid:	No decomposition if used and stored according to specifications.
Possibility of hazardous reactions	Hazardous polymerization will not occur.
Conditions to avoid	Direct sunlight. Extremely high or low temperatures. Contact with metallic substances.
Hazardous decomposition products	Carbon oxides (CO, CO ₂). Sodium oxides.
Materials to avoid	Metals such as aluminum. Reducing agents. Strong acids.
Hazardous polymerization	Will not occur

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Acute toxicity: Harmful if swallowed.

LD/LC50 values relevant for classification:

Diethylene Glycol Monomethyl Ether CAS# 111-90-0:

LD50 (Oral, rat): 19,200 mg/kg

LD50 (Dermal, rabbit): 6 ml/kg

Tributoxy Ethyl Phosphate CAS# 78-51-3:

LD50 (Oral, rat): 3,000 mg/kg

LD50 (Dermal, rabbit): 16 ml/kg

LC50 (Inhalation, rat): >6.4 mg/L 4h

Trimethyl Pentanyl Disobutyrate CAS# 6846-50-0:

LD50 (Oral, rat): 3,200 mg/kg

On the skin: Causes drying of the skin.

Basecoat 456 – Floor Sealer

On the eye: Causes pain and redness.
Respiratory or Skin Sensitization: Not classified.
Additional toxicological information:
Carcinogenicity:
Chemical Name None

12. ECOLOGICAL INFORMATION

Toxicity:	Not classified
Persistence and Degradability:	Not available
Bioaccumulative Potential:	Not available
Mobility in Soil:	Not available.
Other Adverse Effects	
Other Information:	All of the organic components of this product are readily biodegradable.

13. DISPOSAL

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, and international regulations.
Ecology – Waste Materials: Avoid release to the environment.

14. TRANSPORTATION INFORMATION

U.S. Department of Transportation (DOT): Not regulated.
Canadian TDG (Road & Rail): Not regulated.
Water Transportation (IMO): Not regulated.
Air Transportation (IATA): Not regulated.

15. REGULATORY INFORMATION

International Inventories

TSCA	-
DSL/NDSL	-
EINECS/ELINCS	Complies
ENCS	Complies
IECSC	Complies
KECL	-
PICCS	-
AICS	Complies



Basecoat 456 – Floor Sealer

Legend:

TSCA - All components of this product are listed or are exempt or excluded from listing on the United States Toxic Substances Control Act Section 8(b) Inventory.

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances **ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health Hazard	No
Chronic Health Hazard	No
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.



Basecoat 456 – Floor Sealer

U.S. State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations:

This product does not contain substances regulated by state right-to-know regulations.

HMIS III Rating

Health: 0 Minimal Hazard

Flammability: 0 Minimal Hazard

Physical: 0 Minimal Hazard

Personal Protection: B

SDS US (GHS HazCom 2012 and WHMIS 2015)

16. OTHER INFORMATION

Prepared By: Parkside Professional Products Ltd.
4777 Kent Avenue
Niagara Falls, Ontario
L2H 1J5
908-358-8364

Issuing Date: December 23, 2024

Disclaimer:

The manufacturer warrants that this product conforms to its standard specification when used according to direction. To the best of our knowledge the information contained herein is accurate. However, we do not assume accuracy or completeness of the information contained herein.

Final determination of the suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

End of Safety Data Sheet