

FH446 - HYPER LIFT OFF

SECTION 1: IDENTIFICATION

- 1.1 Product identifier:** FH446 - HYPER LIFT OFF
- Other means of identification:**
FH446
Use of Preparation: Floor Finish Strippers
- 1.2 Recommended use of the chemical and restrictions on use:**
Relevant uses (Consumer use): Stripper
Relevant uses (Industrial user): Stripper
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Initial supplier identifier:**
Parkside Professional Products Limited
4777 Kent Avenue
L2H 1J5 Niagara Falls - Ontario - Canada
Phone: 1 (877) 480-8127
info@parkside.com
https://www.parkside.com
- 1.4 Emergency phone number:** 905-358-8364

SECTION 2: HAZARD IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
WHMIS 2022:
Classification of this product has been carried out in accordance with Part 2 of Hazardous Products Regulations (SOR/2015-17 amended by SOR/2022-272)
Acute Tox. 4: Acute inhalation toxicity, Category 4, H332
Acute Tox. 4: Acute toxicity, Category 4, H302+H312
Eye Dam. 1: Serious eye damage, Category 1, H318

2.2 Label elements:

WHMIS 2022:

Danger



Hazard statements:

Acute Tox. 4: H332 - Harmful if inhaled.
Acute Tox. 4: H302 - Harmful if swallowed.
Acute Tox. 4: H312 - Harmful in contact with skin.
Eye Dam. 1: H318 - Causes serious eye damage.

Precautionary statements:

P101: If medical advice is needed, have product container or label at hand.
P102: Keep out of reach of children.
P271: Use only outdoors or in a well-ventilated area.
P280: Wear protective gloves/protective clothing/eye protection/protective footwear.
P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310: Immediately call a POISON CENTER or doctor/physician.
P501: Dispose of contents and / or their container according to the separated collection system used in your municipality.

Additional labeling:



CAUTION

- CONTINUED ON NEXT PAGE -

FH446 - HYPER LIFT OFF

SECTION 2: HAZARD IDENTIFICATION (continued)

CCCR 2001 >> Sub-Category "Harmful": Inhalation
POISON. CONTENTS MAY BE HARMFUL. Do not breathe fumes. Keep out of reach of children. Use only in a well-ventilated area.
FIRST AID TREATMENT

If swallowed, call a Poison Control Centre or doctor immediately. If breathed in, move person into fresh air.
Contains .

2.3 Health and physical hazards not otherwise classified (HHNOC - PHNOC):

Not relevant

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances:

Not relevant

3.2 Mixtures:

Chemical description: Aqueous mixture composed of chemical products for cleaning products

Components:

In accordance with Schedule I of the Hazardous Products Regulations (SOR/2015-17), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 100-51-6	benzyl alcohol Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Sens. 1B: H317 - Warning	30 - <60%
CAS: 141-43-5	2-aminoethanol Acute Tox. 4: H302+H312+H332; Flam. Liq. 4: H227; Skin Corr. 1B: H314 - Danger	30 - <60%
CAS: 111-76-2	2-butoxyethanol Acute Tox. 3: H331; Acute Tox. 4: H302; Eye Irrit. 2: H319; Flam. Liq. 4: H227; Skin Irrit. 2: H315 - Danger	10 - <30%

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST-AID MEASURES

4.1 Description of necessary measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Request medical assistance immediately, showing the SDS of this product. Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. In the case of loss of consciousness do not administrate anything orally unless supervised by a doctor. Rinse out the mouth and throat, as they may have been affected during ingestion. Keep the person affected at rest.

4.2 Most important symptoms/effects, acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of immediate medical attention and special treatment needed, if necessary:

Not relevant

SECTION 5: FIRE-FIGHTING MEASURES

- CONTINUED ON NEXT PAGE -

FH446 - HYPER LIFT OFF

SECTION 5: FIRE-FIGHTING MEASURES (continued)

5.1 Suitable (and unsuitable) extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

Non-applicable

5.2 Specific hazards arising from the chemical:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Special protective equipment and precautions for fire-fighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and Self Contained Breathing Apparatus. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

6.3 Methods and materials for containment and cleaning up:

It is recommended:

Prevent the entrance of product in drains, sewers or watercourses. Absorb the spill using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. Collect the product in appropriate containers and manage it according to current legislation.

Spillages in water or sea:

Small spillages:

Contain spillage using barriers or similar equipment. Use suitable absorbents for collection and treat the waste in accordance with current regulations.

Large spillages:

If possible, contain spillage in open water using barriers or similar equipment. If this is not possible, try to control its spread and collect the product with suitable mechanical means. Always consult experts before using dispersants and make sure you have the necessary approvals if they are to be used. Treat the waste according to current regulations.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

- CONTINUED ON NEXT PAGE -

FH446 - HYPER LIFT OFF

SECTION 7: HANDLING AND STORAGE (continued)

Product is non-flammable under normal conditions of storage, manipulation and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Minimum Temp.: 5 °C

Maximum Temp.: 30 °C

Maximum time: 6 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be assessed in the workplace:

British Columbia - Occupational Health and Safety Regulation section 5.48 (Updated June 22, 2022):

Identification	Occupational exposure limits		
2-aminoethanol ⁽¹⁾ CAS: 141-43-5	TLV-TWA	3 ppm	
	TLV-STEL	6 ppm	
2-butoxyethanol ⁽¹⁾ CAS: 111-76-2	TLV-TWA	20 ppm	
	TLV-STEL		

ALBERTA - Occupational Health and Safety Code:

Identification	Occupational exposure limits		
2-aminoethanol ⁽¹⁾ CAS: 141-43-5	8-hour	3 ppm	7.5 mg/m ³
	15-minute	6 ppm	15 mg/m ³
2-butoxyethanol ⁽¹⁾ CAS: 111-76-2	8-hour	20 ppm	97 mg/m ³
	15-minute		

⁽¹⁾ Skin

8.2 Appropriate engineering controls:

A.- Individual protection measures, such as personal protective equipment


As a preventative measure it is recommended to use basic Personal Protection Equipment. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

If the working conditions and/or safety measures adopted do not allow keeping the airborne concentration of the product below the exposure limits (if any) or at acceptable levels (if no exposure limits exist), suitable respiratory protection equipment chosen by a qualified professional should be used.

C.- Specific protection for the hands

Pictogram	PPE	Remarks
 Mandatory hand protection	Chemical protective gloves (Material: Nitrile, Breakthrough time: > 480 min, Thickness: 0.4 mm)	Replace the gloves at any sign of deterioration.


- CONTINUED ON NEXT PAGE -

FH446 - HYPER LIFT OFF

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Remarks
 Mandatory face protection	Panoramic glasses against splash/projections.	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Bodily protection

Pictogram	PPE	Remarks
	Work clothing	Replace before any evidence of deterioration.
	Anti-slip work shoes	Replace before any evidence of deterioration.

F.- Additional emergency measures

It is advised to implement additional emergency equipments in workplaces that are particularly exposed to the product or in situations where risk assessments highlight the necessity of such equipments.

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

To comply with environmental protection regulations, it is recommended to prevent any spillage of the product and its container. For more detailed information, please refer to subsection 7.1.D.

Volatile organic compounds (VOC) according to Canadian Environmental Protection Act, 1999:

Volatile organic compounds: 97 % weight
V.O.C. density at 20 °C: 971.1 kg/m³ (971.1 g/L)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C: Liquid
Appearance: Transparent
Colour: Amber
Odour: Mild
Odour threshold: Not relevant *

Volatility:

Boiling point or initial boiling point and boiling range: 182 °C
Vapour pressure at 20 °C: 136 Pa
Vapour pressure at 50 °C: 836.27 Pa (0.84 kPa)
Evaporation rate at 20 °C: Not relevant *

Product description:

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

FH446 - HYPER LIFT OFF

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Density at 20 °C:	1001.1 kg/m ³
Relative density at 20 °C:	1.001
Dynamic viscosity at 20 °C:	Not relevant *
Kinematic viscosity at 20 °C:	Not relevant *
Kinematic viscosity at 40 °C:	Not relevant *
Concentration:	Not relevant *
pH:	12.5 - 13.5
Relative vapour density at 20 °C:	Not relevant *
Partition coefficient — n-octanol/water (logarithmic value) 20 °C:	Not relevant *
Solubility in water at 20 °C:	Not relevant *
Solubility properties:	Completely soluble
Decomposition temperature:	Not relevant *
Melting point/freezing point:	Not relevant *
Flammability:	
Flash Point:	87 °C
Flammability (solid, gas):	Not relevant *
Autoignition temperature:	238 °C
Lower flammability limit:	Not relevant *
Upper flammability limit:	Not relevant *
Particle characteristics:	
Median equivalent diameter:	Not relevant *

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:	Not relevant *
Oxidising properties:	Not relevant *
Corrosive to metals:	Not relevant *
Heat of combustion:	Not relevant *
Aerosols-total percentage (by mass) of flammable components:	Not relevant *

Other safety characteristics:

Surface tension at 20 °C:	Not relevant *
Refraction index:	Not relevant *
MIR (Maximum Incremental Reactivity):	3.11

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

- CONTINUED ON NEXT PAGE -

FH446 - HYPER LIFT OFF

SECTION 10: STABILITY AND REACTIVITY (continued)

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Precaution	Precaution	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Not applicable

10.6 Hazardous decomposition products:

Contains substances which require external energy for spontaneous decomposition. Form explosive peroxides when distilled, evaporated or otherwise concentrated.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. With possibility of effects that are hazardous to the health, it is recommended not to breathe the vapours for long periods of time.

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Exposure in high concentration can cause a breakdown in the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Above all, may have harmful effects for health if the product is absorbed through the skin. For more information on the secondary effects of contact with the skin see section 2.
- Contact with the eyes: Produces serious eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
IARC: 2-butoxyethanol (3: Not classifiable as to its carcinogenicity to humans)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous with sensitising effects. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

- CONTINUED ON NEXT PAGE -

FH446 - HYPER LIFT OFF

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Not relevant

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
2-aminoethanol CAS: 141-43-5	LD50 oral	1089 mg/kg	Rat
	LD50 dermal	1100 mg/kg	
	LC50 inhalation vapour	11 mg/L	
2-butoxyethanol CAS: 111-76-2	LD50 oral	1200 mg/kg	Rat
	LD50 dermal		
	LC50 inhalation vapour	3 mg/L	
benzyl alcohol CAS: 100-51-6	LD50 oral	1200 mg/kg	
	LD50 dermal		
	LC50 inhalation vapour		

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

12.1 Ecotoxicity (aquatic and terrestrial, where available):

Acute toxicity:

Identification	Concentration	Species	Genus
2-aminoethanol CAS: 141-43-5	LC50 349 mg/L (96 h)	Cyprinus carpio	Fish
	EC50 65 mg/L (48 h)	Daphnia magna	Crustacean
	EC50 22 mg/L (72 h)	Scenedesmus subspicatus	Algae
2-butoxyethanol CAS: 111-76-2	LC50 1490 mg/L (96 h)	Lepomis macrochirus	Fish
	EC50 1815 mg/L (48 h)	Daphnia magna	Crustacean
	EC50 911 mg/L (72 h)	Pseudokirchneriella subcapitata	Algae

Chronic toxicity:

Identification	Concentration	Species	Genus
2-aminoethanol CAS: 141-43-5	NOEC 1.24 mg/L	Oryzias latipes	Fish
	NOEC 0.85 mg/L	Daphnia magna	Crustacean
2-butoxyethanol CAS: 111-76-2	NOEC 100 mg/L	Danio rerio	Fish
	NOEC 100 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability		Biodegradability	
benzyl alcohol CAS: 100-51-6	BOD5	Not relevant	Concentration	100 mg/L
	COD	Not relevant	Period	14 days
	BOD5/COD	Not relevant	% Biodegradable	94 %
2-aminoethanol CAS: 141-43-5	BOD5	Not relevant	Concentration	20 mg/L
	COD	Not relevant	Period	21 days
	BOD5/COD	Not relevant	% Biodegradable	90 %
2-butoxyethanol CAS: 111-76-2	BOD5	0.71 g O2/g	Concentration	100 mg/L
	COD	2.2 g O2/g	Period	14 days
	BOD5/COD	0.32	% Biodegradable	96 %

12.3 Bioaccumulative potential:

Substance-specific information:

- CONTINUED ON NEXT PAGE -

FH446 - HYPER LIFT OFF

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Bioaccumulation potential	
benzyl alcohol CAS: 100-51-6	BCF	1
	Pow Log	1.05
	Potential	Low
2-aminoethanol CAS: 141-43-5	BCF	3
	Pow Log	-1.31
	Potential	Low
2-butoxyethanol CAS: 111-76-2	BCF	3
	Pow Log	0.83
	Potential	Low

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
benzyl alcohol CAS: 100-51-6	Koc	15.7	Henry	8.8E-2 Pa·m ³ /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	3.679E-2 N/m (25 °C)	Moist soil	Yes
2-aminoethanol CAS: 141-43-5	Koc	0.27	Henry	3.7E-5 Pa·m ³ /mol
	Conclusion	Very High	Dry soil	Not relevant
	Surface tension	5.025E-2 N/m (25 °C)	Moist soil	Not relevant
2-butoxyethanol CAS: 111-76-2	Koc	8	Henry	1.621E-1 Pa·m ³ /mol
	Conclusion	Very High	Dry soil	Not relevant
	Surface tension	2.729E-2 N/m (25 °C)	Moist soil	Yes

12.5 Results of PBT and vPvB assessment:

Not relevant

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Disposal methods:

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations. In case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See epigraph 6.2.

Regulations related to waste management:

Legislation related to waste management:

Canadian Environmental Protection Act, 1999

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to Transportation of Dangerous Goods Regulations (SOR/2001-286) including Amendments:

FH446 - HYPER LIFT OFF

SECTION 14: TRANSPORT INFORMATION (continued)



- 14.1 UN number:** UN3267
- 14.2 United Nations proper shipping name:** CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (2-aminoethanol)
- 14.3 Transport hazard class(es):** 8
Labels: 8
- 14.4 Packing group:** III
- 14.5 Environmental hazard:** No
- 14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises**
Physico-Chemical properties: see section 9
- 14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):** Not relevant

Transport of dangerous goods by sea:

With regard to IMDG 42-24:



- 14.1 UN number:** UN3267
- 14.2 United Nations proper shipping name:** CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (2-aminoethanol)
- 14.3 Transport hazard class(es):** 8
Labels: 8
- 14.4 Packing group:** III
- 14.5 Marine pollutant:** No
- 14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises**
Special regulations: 274, 223
EmS Codes: F-A, S-B
Physico-Chemical properties: see section 9
Limited quantities: 5 L
Segregation group: SGG18
- 14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):** Not relevant

Transport of dangerous goods by air:

With regard to IATA/ICAO 2026:



- 14.1 UN number:** UN3267
- 14.2 United Nations proper shipping name:** CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (2-aminoethanol)
- 14.3 Transport hazard class(es):** 8
Labels: 8
- 14.4 Packing group:** III
- 14.5 Environmental hazard:** No
- 14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises**
Physico-Chemical properties: see section 9
- 14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):** Not relevant

SECTION 15: REGULATORY INFORMATION

- 15.1 Safety, health and environmental regulations specific for the product in question:**

FH446 - HYPER LIFT OFF

SECTION 15: REGULATORY INFORMATION (continued)

- Domestic Substances List (DSL): *benzyl alcohol (100-51-6)*; *2-aminoethanol (141-43-5)*; *2-butoxyethanol (111-76-2)*
- Export control list: Part 1: prohibited substances: Not relevant
- Export control list: Part 2: substances subject to notification or consent: Not relevant
- Export control list: Part 3: restricted substances: Not relevant
- First Priority Substances List (PSL1): Not relevant
- National Pollutant Release Inventory (NPRI) 2025- 2027 substance list: *2-butoxyethanol (111-76-2)*
- Non-Domestic Substances List (NDSL): Not relevant
- Plan of Priorities (Substances identified as priorities for assessment): Not relevant
- Prohibition of Certain Toxic Substances Regulations, 2012: Not relevant
- Second Priority Substances List (PSL2): Not relevant
- Toxic substances list: Part 1: Not relevant
- Toxic substances list: Part 2: *2-butoxyethanol (111-76-2)*
- Virtual Elimination List: Not relevant

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information provided in this safety data sheet as a foundation for conducting workplace-specific risk assessments. These assessments will help establish the appropriate risk prevention measures for handling, using, storing, and disposing of this product.

Other legislation:

Canadian Environmental Protection Act, 1999

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with Part 4 and Schedule I of the Hazardous Products Regulations (SOR/2015-17), amended by SOR/2020-38 and SOR/2022-272.

Texts of the legislative phrases mentioned in section 2:

H332: Harmful if inhaled.

H318: Causes serious eye damage.

H302+H312: Harmful if swallowed or in contact with skin.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

WHMIS 2022:

Acute Tox. 3: H331 - Toxic if inhaled.

Acute Tox. 4: H302 - Harmful if swallowed.

Acute Tox. 4: H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Liq. 4: H227 - Combustible liquid.

Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1B: H317 - May cause an allergic skin reaction.

Advice related to training:

Minimal training is recommended to prevent industrial risks for staff using this product, in order to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://whmis.org/>

Abbreviations and acronyms:

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor LD50: Lethal Dose 50 CL50: Lethal Concentration 50

EC50: Effective concentration 50

Log-POW: Octanol-water partition coefficient

Koc: Partition coefficient of organic carbon

IARC: International Agency for Research on Cancer

Date of compilation: 2026-04-23

- CONTINUED ON NEXT PAGE -



Safety data sheet
According to WHMIS 2022 (SOR/2022-272)

FH446 - HYPER LIFT OFF

Disclaimer:

The information contained in this Safety Data Sheets (SDS) is subject to change without notice. Product formulation changes and WHMIS and TDG updates may cause the related documentation to be updated periodically.

The manufacturer warrants that this product conforms to its standard specification when used according to direction. To the best of our knowledge the information contained herein is accurate. However, we do not assume accuracy or completeness of the information contained herein.

Final determination of the suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. If you have a question about the contents of this SDS, or require technical assistance, please contact Customer Service.

END OF SAFETY DATA SHEET