



Vestec 762 – Powder Rust & Scale Remover

1. IDENTIFICATION OF THE SUBSTANCE OR PREPARATION AND OF THE COMPANY

Identification of Preparation:	Vestec 762
Date of Safety Data Sheet:	October 23, 2017
Use of Preparation:	Powder Rust Remover
Company Identification:	Parkside Professional Products Ltd. 4777 Kent Avenue Niagara Falls, Ontario L2H 1J5 OFFICE: 905-358-8364
Company Emergency Telephone Number	Emergency Phone: 905-358-8364
Transportation Emergency Telephone Number	CANUTEC 613-996-6666 or * 666 for cell phone

2. HAZARD IDENTIFICATION

Emergency Overview:
 OSHA / WHMIS 2015 Hazards
 Classification of substance or mixture
 GHS-US/Canadian classification:
 GHS Hazards
 Acute Toxicity (Oral) Category 4 H302
 Skin Corrosive Category 1B H314
 Eye Damage Category 1 H318
 Label Elements
 GHS-US/ Canada Labeling
 Hazard Pictograms (GHS):



Signal Word (GHS): Danger
 Hazard Statements (GHS):
 H302: Harmful if swallowed.
 H314: Causes severe skin burns and eye damage
 H318: Causes serious eye damage



Vestec 762 – Powder Rust & Scale Remover

Precautionary Statements (GHS):

P264: Wash exposed skin thoroughly after handling.

P280: Wear face protection, protective clothing, protective gloves, and eye protection.

Response Statements (GHS):

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention.

P363: Wash contaminated clothing before reuse.

P405: Store locked up.

P501: Dispose of contents / container in accordance with local regulations.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Description: Chemical Blend

Ingredient	CAS#	% by Wt	Classification
Oxalic Acid	144-62-7	90-100	Skin Corrosion/Irritation Category 1B - H314 Serious Eye Damage/Eye Irritation Category 1 - H318

4. FIRST AID MEASURES

Inhalation:	Remove to fresh air and keep at rest in a position comfortable for breathing.
Eye Contact:	Remove contacts. Flush with water for at least 20 minutes, occasionally lifting the upper and lower eyelids. Repeat if required. Immediately call a POISON CENTRE or doctor/physician.
Skin Contact:	Thoroughly wash exposed skin with water. Remove any contaminated clothing and wash before reuse.
Ingestion:	Wash out mouth with water. Drink plenty of water. Do not induce vomiting unless directed by medical personal. Never give anything to an unconscious person. Immediately call a POISON CENTRE or doctor/physician.
Notes to Physician:	Treatment based on judgment of attending physician. Gastric lavage is not recommended.
Most Important symptoms and effects, both acute and delayed:	Caustic burns/corrosion to the skin. Dry/red skin. Corrosion of the eye tissue. Nausea. Abdominal pain. Blood in vomit. Burns to gastric/intestinal mucous.

5. FIRE FIGHTING MEASURES

Suitable extinguishing media:	Water spray for extinguishing agent. CO ₂ , dry chemical, alcohol resistant foam, sand.
Unsuitable extinguishing media:	None known. Do not use a heavy stream of water.



Vestec 762 – Powder Rust & Scale Remover

Special exposure hazards	Thermal decomposition releases corrosive vapours. Decomposes on exposure to temperature rise.
Special safety equipment:	Self-contained positive pressure breathing apparatus and protective clothing.
Fire and explosion	Not flammable. Not an explosive hazard.
Further information	Keep containers and surrounding cool with water spray.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not get in eyes, on skin, or on clothing. Do not breathe vapour or mist.

For Non-Emergency Personnel:

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel:

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area.

Environmental Precautions

Prevent entry to sewers and public waters

Methods and Material for Containment and Cleaning Up:

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clear up spills immediately with absorbent and dispose of waste safely.

Reference to Other Sections: See Heading 8. Exposure controls and personal protection.

7. HANDLING AND STORAGE

Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Do not breathe mist, vapours, spray.

Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Information about fire and explosion protection:

Keep respiratory protective device available.

No special measures required.

Conditions for safe storage, including any incompatibilities:

Storage: Oxidizers, reducing agents, strong bases and metals.

Requirements to be met by storerooms and receptacles:

Store in a cool location.

Information about storage in one common storage facility:

Do not store together with alkaline products, oxidizers or reducing agents.

Store away from foodstuffs.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Store receptacle in a well-ventilated area.

Keep container tightly sealed.

Specific end use(s) No further relevant information available.



Vestec 762 – Powder Rust & Scale Remover

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Appropriate Engineering Controls:

Engineering Measures Showers. Eyewash Stations. Ventilation Systems.

Individual Protection Measures:

Respiratory protection: Use local exhaust or dilution ventilation.
 Hand protection: Chemical resistant gloves.
 Eye protection: Safety goggles or full-face shield.
 Skin protection: Use body-covering impervious clothing.
 Working hygiene: Take usual precautions when handling. Workers should wash hands before eating, drinking or smoking.

Exposure Guidelines: **Oxalic Acid**
 OSHA PEL TWA 1 mg/m³
 NIOSH REL: TWA 1 mg/m³ ST 2 mg/m³

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

<u>Property</u>	<u>Values</u>	<u>Remarks/Method</u>	<u>Odour</u>
Physical State	Powder		
Appearance	Free flowing		Typical.
Colour	White		No data available.
<u>Property</u>	<u>Values</u>	<u>Remarks/Method</u>	
pH(1.0% solution)	1.30	None known	
Melting/Freezing Point	No data available	None known	
Boiling Point/Range	No data available	None known	
Flash Point	Not applicable.	None known	
Evaporation Rate	Similar	None known	
Flammability (solid, gas)	Not flammable	None known	
Flammability Limit in Air:	Not flammable		
Upper Limit	No data available	None known	
Lower Limit	No data available	None known	
Vapour Pressure	No data available	None known	
Vapour density	No data available	None known	
Specific Gravity	No data available		
Water Solubility	Soluble in water.	None known	
Solubility Other Solvents	No data available	None known	
Partition Coefficient:			
n-octanol/water	No data available	None known	



Vestec 762 – Powder Rust & Scale Remover

Autoignition temperature	No data available	None known
Decomposition Temperature	No data available	None known
Kinematic Viscosity	No data available	None known
Dynamic Viscosity	No data available	None known
Explosive Properties	No data available	None known
Oxidizing Properties	No data available	None known

Other Properties:

Softening Point	No data available
VOC Content %	No data available
Particle Size	No data available
Particle Size Distribution	No data available

10. STABILITY AND REACTIVITY

Reactivity	Violent exothermic reaction with (some) bases. Violent to explosive reaction with many compounds e.g.: with (strong) oxidizers and with (strong) reducers.
Chemical stability	Stable under recommended handling and storage conditions (see section 7).
Thermal decomposition/conditions to avoid:	No decomposition if used and stored according to specifications.
Possibility of hazardous reactions	Not established.
Conditions to avoid	Direct sunlight. Extremely high or low temperatures. Contact with metallic substances.
Hazardous decomposition products	Carbon oxides (CO, CO ₂). Sodium oxides. Carbon monoxide. Carbon dioxide. Thermal decomposition generates: corrosive vapours.
Materials to avoid	Reducing agents. Strong acids. Strong bases. Cyanides
Hazardous polymerization	Will not occur

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Acute toxicity: oral 375.00 mg/kg, Harmful if swallowed.

LD/LC50 values relevant for classification: 375 mg/kg Oral Rat, +20000 mg/kg Dermal Rat, 1100 mg/kg Dermal

On the skin: Causes severe skin irritation & corrosive injury.

On the eye: Causes serious eye damage, prolong contact can cause irreversible eye damage.

Respiratory or Skin Sensitization: Not classified.

Ingestion: Can cause severe poisoning or death depending on concentration.

Additional toxicological information: no information available

Carcinogenicity: no information available

Chemical Name: Oxalic Acid



Vestec 762 – Powder Rust & Scale Remover

12. ECOLOGICAL INFORMATION

Toxicity:	Not available
Persistence and Degradability:	Not available
Bioaccumulative Potential:	Not available
Mobility in Soil:	Not available
Other Adverse Effects	Not available
Other Information:	Avoid release to the environment.

13. DISPOSAL

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, and international regulations.

Ecology – Waste Materials: Avoid release to the environment.

14. TRANSPORTATION INFORMATION

Canadian T.D.G.: Not Regulated

15. REGULATORY INFORMATION

Occupational Health & Safety Regulations:

WHMIS 1988 Classification: Class D - Division 2B, Class E



OSHA & WHMIS: MSDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200) and Canadian WHMIS regulations (Controlled Products Regulations under the Hazardous Products Act).

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Complies
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

Legend:

TSCA - All components of this product are listed or are exempt or excluded from listing on the United States Toxic Substances Control Act Section 8(b) Inventory.

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List



Vestec 762 – Powder Rust & Scale Remover

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

California Proposition 65

This product does not contain any Proposition 65 chemicals.

HMIS III Rating

Health: 3 Serious Hazard

Flammability: 0 Minimal Hazard

Physical: 0 Minimal Hazard

Personal Protection: B

SDS US (GHS HazCom 2012 and WHMIS 2015)

16. OTHER INFORMATION

Prepared By: Parkside Professional Products Ltd.
4777 Kent Avenue
Niagara Falls, Ontario
L2H 1J5
905-358-8364

Issuing Date: October 23, 2017

Disclaimer:

The manufacturer warrants that this product conforms to its standard specification when used according to direction. To the best of our knowledge the information contained herein is accurate. However, we do not assume accuracy or completeness of the information contained herein.

Final determination of the suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

End of Safety Data Sheet