

Vestec 452 – Metal-Safe Pre-Soak

1. IDENTIFICATION OF THE SUBSTANCE OR PREPARATION AND OF THE COMPANY

Identification of Preparation:	Vestec 452
Date of Safety Data Sheet:	August 28, 2025
Use of Preparation:	Metal-Safe Presoak
Company Identification:	Parkside Professional Products Ltd. 4777 Kent Avenue Niagara Falls, Ontario L2H 1J5 OFFICE: 905-358-8364
Company Emergency Telephone Number	Emergency Phone: 905-358-8364.
Transportation Emergency Telephone Number	CANUTEC 613-996-6666 or * 666 for cell phone

2. HAZARD IDENTIFICATION

Emergency Overview:

OSHA / WHMIS 2015 Hazards

Irritant.

Classification of substance or mixture

GHS-US/Canadian classification:

GHS Hazards

Acute Toxicity Category 4 (Oral) H302

Skin Irritation Category 2 H315

Eye Irritation Category 2A H319

Label Elements

GHS Labeling

Hazard Pictograms (GHS):



Signal Word (GHS): Warning

Hazard Statements (GHS):

H302: Harmful if swallowed.

H315: Causes skin irritation.

H319: Causes serious eye irritation.



Vestec 452 – Metal-Safe Pre-Soak

Precautionary Statements (GHS):

P264: Wash hands thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response Statements (GHS):

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Description: Chemical Blend

Ingredient	CAS#	% by Wt	Classification
Sodium Carbonate	497-19-8	30-60	Acute Toxicity Category 4 (Oral) - H302 Skin Corrosion / Irritation Category 2 - H315 Serious Eye Damage/Irritation Category 2A - H319
Fatty Alcohol Ethoxylate	68991-48-0	1-5	Serious Eye Damage/Irritation Category 2A - H319

4. FIRST AID MEASURES

Inhalation: Remove to fresh air. If symptoms persist consult physician.

Eye Contact: Remove contacts. Flush with water for at least 20 minutes, occasionally lifting the upper and lower eyelids. Repeat if required. If irritation persists get medical attention.

Skin Contact: Thoroughly wash exposed skin with soap and water. Remove any contaminated clothing and wash before reuse.

Ingestion: Wash out mouth with water. Drink plenty of water. Do not induce vomiting unless directed by medical personal. Never give anything to an unconscious person. Get medical aid.

Notes to Physician: Treatment based on judgment of attending physician.

5. FIRE FIGHTING MEASURES

Suitable extinguishing media: As per surrounding fire.

Unsuitable extinguishing media: No information available.

Special exposure hazards Fire or excessive heat may produce hazardous decomposition products.

Special safety equipment: Self-contained positive pressure breathing apparatus and protective clothing.

Fire and explosion Not flammable. Not an explosive hazard.

Further information Keep containers and surrounding cool with water spray.

Vestec 452 – Metal-Safe Pre-Soak

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not get in eyes, on skin, or on clothing. Do not breathe mist or dust.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area.

Environmental Precautions

Prevent entry to sewers and public waters.

Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clear up spills immediately by sweeping up and dispose of waste safely.

Reference to Other Sections: See Heading 8. Exposure controls and personal protection.

7. HANDLING AND STORAGE

Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of mist.

Information about fire - and explosion protection:

Keep respiratory protective device available.

No special measures required.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Store in a cool location.

Information about storage in one common storage facility:

Do not store together with acid products.

Store away from reducing agents.

Store away from foodstuffs.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Store receptacle in a well-ventilated area.

Keep container tightly sealed.

Specific end use(s) No further relevant information available.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection: Use local exhaust or dilution ventilation.

Hand protection: Chemical resistant gloves.

Eye protection: Safety goggles.

Skin protection: Use body-covering clothing.

Working hygiene: Take usual precautions when handling. Workers should wash hands before eating, drinking or smoking.

Vestec 452 – Metal-Safe Pre-Soak
Exposure Guidelines:

Source Material	TWA ppm	TWA mg/m³	STEL ppm	STEL mg/m³
Sodium Carbonate		15 mg/m ³ 8 hr (dust)		

9. PHYSICAL AND CHEMICAL PROPERTIES
Physical and Chemical Properties

Physical State	Powder	Odour	Mild
Appearance	Free Flowing.	Odour Threshold	No data available.
Colour	White	Remarks/Method	
Property	Values		
pH 1 %	11.50-12.50	None known	
Melting/Freezing Point	No data available	None known	
Boiling Point/Range	No data available	None known	
Flash Point	Not applicable.	None known	
Evaporation Rate	No data available	None known	
Flammability (solid, gas)	Not flammable	None known	
Flammability Limit in Air:			
Upper Limit	No data available	None known	
Lower Limit	No data available	None known	
Vapour Pressure	No data available	None known	
Vapour density	No data available	None known	
Specific Gravity	0.85-0.95 g/cm ³		
Water Solubility	Soluble in water.	None known	
Solubility Other Solvents	No data available	None known	
Partition Coefficient:			
n-octanol/water	No data available	None known	
Autoignition temperature	No data available	None known	
Decomposition	No data available	None known	
Temperature			
Kinematic Viscosity	No data available	None known	
Dynamic Viscosity	No data available	None known	
Explosive Properties	No data available	None known	
Oxidizing Properties	No data available	None known	
Other Properties:			
Softening Point	No data available		
VOC Content %	No data available		
Particle Size	No data available		
Particle Size Distribution	No data available		

Vestec 452 – Metal-Safe Pre-Soak

10. STABILITY AND REACTIVITY

Reactivity	Stable at normal ambient temperature and pressure.
Chemical stability	No decomposition if stored and applied as directed.
Thermal decomposition/conditions to avoid:	Stable under normal conditions.
Possibility of hazardous reactions	Reacts with acids. Reacts with reducing and oxidizing agents.
Conditions to avoid	Store away from reducing agents, water, acids, and acid salts of heavy metals, organic materials and flammable substances.
Hazardous decomposition products	Acids, oxidizing and reducing agents.
Materials to avoid	Oxides of carbon.
Hazardous polymerization	Will not occur

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects
Acute toxicity:
LD/LC50 values relevant for classification
Routes of Entry Inhalation, ingestion, eye or skin
Sodium Carbonate CAS # 497-19-8:
 LD 50 (Oral) Rat 4,090 mg/Kg
Fatty Alcohol Ethoxylate CAS# 68991-48-0:
 LD50 (Oral) Rat 2,000 mg/Kg
Carcinogenicity:

Chemical Name	ACGIH	IARC	NTP	OSHA
Not classified.				

IARC: (International Agency for Research on Cancer)
 No ingredients listed
Chronic Effects:
Mutagenicity: No evidence of a mutagenic effect.
Teratogenicity: No evidence of a teratogenic effect (birth defect).
Sensitization: No evidence of a sensitization effect.
Reproductive: No evidence of negative reproductive effects.
Target Organ Effects:
Acute: No information available

12. ECOLOGICAL INFORMATION

Toxicity:	Not classified
Persistence and Degradability:	Not available
Bioaccumulative Potential:	Not available
Mobility in Soil:	Not available.
Other Adverse Effects	Avoid release to the environment.
Other Information:	All of the organic components of this product are readily biodegradable.

Vestec 452 – Metal-Safe Pre-Soak

13. DISPOSAL

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, and international regulations.

Ecology – Waste Materials: Avoid release to the environment.

14. TRANSPORTATION INFORMATION

Canadian TDG (Road & Rail): Not Regulated

U.S. Department of Transportation (DOT): Not Regulated

Water Transportation (IMO): Not Regulated

Air Transportation (IATA): Not Regulated

15. REGULATION

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Complies
IECSC	Complies
KECL	Complies
PICCS	Complies -
AICS	Complies

Legend:

TSCA - All components of this product are listed or are exempt or excluded from listing on the United States Toxic Substances Control Act Section 8(b) Inventory.

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

U.S. State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.



Vestec 452 – Metal-Safe Pre-Soak

HMIS III Rating:

Health: 1 Slight Hazard - Irritation or minor reversible injury possible

Flammability: 0 Minimal Hazard

Physical: 0 Minimal Hazard

Personal Protection: B

SDS US (GHS HazCom 2012) SDS Canada (GHS WHMIS 2015)

16. OTHER INFORMATION

Prepared By: Parkside Professional Products Ltd.
4777 Kent Avenue
Niagara Falls, Ontario
L2H 1J5
905-358-8364

Issuing Date: August 28, 2025

Disclaimer:

The manufacturer warrants that this product conforms to its standard specification when used according to direction. To the best of our knowledge the information contained herein is accurate. However, we do not assume accuracy or completeness of the information contained herein.

Final determination of the suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

End of Safety Data Sheet